



Hoisting Unit		
Electric hoist	type	MHL6-25 2/1 H12 V8
Capacity	t	5,0
Rope	mm	Φ15
Mode of operation	---	2m
Lifting height	m	12,0
Lifting speed	m/min	8
Output	kW	8,0
Speed of revolution	min ⁻¹	920
Current	A	24,5
Travelling Mechanism		
Travelling speed	m/min	20
Output	kW	2 x 0,37
Speed of revolution	min ⁻¹	905
Current	A	2 x 1,45
Travel wheel diameter	mm	160
Travel wheel max. pressure	t	1,5
Power supply	---	3ph / 400V / 50Hz
Control	---	pendant
Operation	---	indoor

Изм.	Брой	Номер	Подпис	Дата	Озн. на граповост БАС-ISO 1302: Ra	Озн. на формата и разп. БАС-ISO 1101 - 1	Неозн. допуски БАС-ISO 2768
Разраб.	Татарлиев			17.3.2021	ISO 128	Маса (kg) 654.22	Материал:
Проверил					Лист 1/1	 Кат. №: Черт№: EKN20 MHL6-25 2/1 H12 V8	
Утвърдил	Кавалов						
Мащаб	1:10				Monorail trolley, standard headroom- Reeving 2/1		