



Travelling Mechanism		
Travelling speed	m/min	20
Motor	type	KK 1405-6A
Output	kw	0,25
Speed of revolution	min <sup>-1</sup>	870
Current	A	1,0
Travel wheel diameter	mm	125
Travel wheel max.pressure	t	0,93
Power supply	---	3Ph/400V/50Hz
Control	---	pendant
Operation	---	indoor

Hoisting Unit		
Electric hoist	type	МН 5-16 2/1 H6 V8C
Capacity	t	3,2
Mode of operation	---	2m
Lifting height	m	6
Lifting speed	m/min	8
Rope	mm	Ø 12
Output	kw	4,5
Speed of revolution	min <sup>-1</sup>	920
Current	A	12,3

Изм.	Брой	Номер	Подпис	Дата
Разраб.	Иванова			10.11.17
Проверил	Татарлиев			10.11.17
Утвърдил	Кавалов			10.11.17

Озн. на граповост	Озн. на формата и разп.	Неозн. допуски
БАС-ISO 1302: Ra	БАС-ISO 1101 - 1	БАС-ISO 2768
ISO 128	Маса (kg)	Материал:
Лист 1/1	517.87	
		Кат. №:
		Черт№:
<b>Monorail trolley standart headroom</b>		<b>EKN 20 МН 5-16 2/1 H6 V8C</b>