



1. Stationary electric hoists execution A are made with openings 4 x  $\phi 28$ ; 4 x  $\phi 25$  and threaded openings 4 x M27.
2. Stationary electric hoists execution A1 are made only with openings 4 x  $\phi 25$ .
3. Stationary electric hoists execution A2 are made only with threaded openings 4 x M27.
4. Stationary electric hoists execution A3 are made only with openings 4 x  $\phi 28$ .

Electric hoist	type	MH 7-40 4/1 H12 V4
Capacity	t	16,0
Mode of operation	---	2m
Lifting height	m	12
Lifting speed	m/min	4
Rope	mm	$\phi 18$
Output	kw	12,5
Speed of revolution	min <sup>-1</sup>	920
Current	A	36,0

					Озн. на грапавост БДС-ISO 1302: Ra		Озн. на формата и разп. БДС-ISO 1101 - 1		Неозн. допуски БДС-ISO 2768		
					ISO 128 		Маса (kg)				
Изм.	Брой	Номер	Подпис	Дата	Лист 1/1		 balkanarpodem				
Разраб.	Иванова		20.11.15								
Проверил	Татарлиев		20.11.15								
Утвърдил	Кавалов		20.11.15								
Мащаб					<b>1:15</b> <b>Stationary electric hoist</b>					Черт№:	