



| Hoisting Unit | | |
|---------------------|-------------------|----------------------|
| Electric hoist | type | MHL6-25 4/1 H9 V4 |
| Capacity | t | 10,0 |
| Mode of operation | FEM 9.511 | 2m |
| Lifting height | m | 9 |
| Dia. rope | mm | 15 |
| Lifting speed | m/min | 4 |
| Output | kW | 8,0 |
| Speed of revolution | min ⁻¹ | 900 |
| Current | A | 19,1 |
| Power supply | --- | 3 ph / 400 V / 50 Hz |
| Control | --- | pendant |
| Operation | --- | indoor |

| | | | | | Озн. на грапавост БДС-ISO 1302: Ra | Озн. на формата и разп. БДС-ISO 1101-1 | Неозн. допуски БДС-ISO 2768 |
|--|-----------|-------|----------|------|---------------------------------------|---|--------------------------------|
| | | | | | БДС-ISO 128 | Маса (kg) 663.69 | Материал: |
| Изм. | Брой | Номер | Подпис | Дата | | | balkancarpodem |
| Разр. | Татарлиев | | 3.2.2022 | Лист | | | |
| Пров. | | | 3.2.2022 | 1/1 | | | |
| Утв. | Кавалов | | 3.2.2022 | | | | |
| Наименование: | | | | | Мащаб | Кат. №: | |
| Stationary electric wire rope hoist - Reeving 4/1 | | | | | 1:10 | Чертеж №: MHL6-25 4/1 H9 V4C | |