



Travelling Mechanism		
Travelling speed	m/min	20
Geared motor	type	TP160/13 AT71A-2R
Gear ratio	i	13
Output	kW	0,37
Speed of revolution	min <sup>-1</sup>	2800
Current	A	1,0
Travel wheel diameter	mm	100
Travel wheel max. pressure	t	1,0
Power supply	---	3 ph / 400V / 50Hz
Control	---	pendant
Operation	---	indoor

Hoisting Unit		
Electric hoist	type	MH3-08 4/1 H6,5 V4
Capacity	t	3,2
Mode of operation	FEM9.511	2m
Lifting height	m	6,5
Dia. rope	mm	7
Lifting speed	m/min	4
Output	kW	2,2
Speed of revolution	min <sup>-1</sup>	940
Current	A	5,9

					Озн. на граваост БДС-ISO 1302: Ra	Озн. на формата и разп. БДС-ISO 1101-1	Неозн. допуски БДС-ISO 2768
					БДС-ISO 128	Маса (kg) 256.46	Материал:
Изм.	Брой	Номер	Подпис	Дата			<b>balkancarpodem</b>
Разр.	Татарлиев		4.2.2022	Лист			
Пров.			4.2.2022	1/1			
Утв.	Кавалов		4.2.2022				
Наименование:					Мащаб	Кат. №:	
<b>Monorail trolley, reduced headroom - Reeving 4/1</b>					1:10	Чертеж №: ЕКК20 MH3-08 4/1 H6,5 V4	