


| Travelling Mechanism | | |
|---------------------------|-------------------|---------------|
| Travelling speed | m/min | 20 |
| Motor | type | KK 1405-6A |
| Output | kw | 0,25 |
| Speed of revolution | min ⁻¹ | 870 |
| Current | A | 1,0 |
| Travel wheel diameter | mm | 125 |
| Travel wheel max.pressure | t | 0,93 |
| Power supply | --- | 3Ph/400V/50Hz |
| Control | --- | pendant |
| Operation | --- | indoor |

| Hoisting Unit | | |
|---------------------|-------------------|---------------------|
| Electric hoist | type | MH 5-16 2/1 H12 V8C |
| Capacity | t | 3,2 |
| Mode of operation | --- | 2m |
| Lifting height | m | 12 |
| Lifting speed | m/min | 8 |
| Rope | mm | Ø 12 |
| Output | kw | 4,5 |
| Speed of revolution | min ⁻¹ | 920 |
| Current | A | 12,3 |

| Изм. | Брой | Номер | Подпис | Дата |
|--------------|-----------|-------|--------|----------|
| Разраб. | Иванова | | | 10.11.17 |
| Проверил | Татарлиев | | | 10.11.17 |
| Утвърдил | Кавалов | | | 10.11.17 |
| Мащаб | | | | |
| 1:10 | | | | |

| Озн. на граповост | | Озн. на формата и разп. | | Неозн. допуски | |
|-------------------|---|-----------------------------------|--|----------------|--|
| БАС-ISO 1302: Ra | | БАС-ISO 1101 - 1 | | БАС-ISO 2768 | |
| ISO 128 | Маса (kg) | Материал: | | | |
| ISO 128 | 547.42 | | | | |
| Лист 1/1 |  | | | | |
| Кат. №: | | ЕКН 20 MH 5-16 2/1 H12 V8C | | | |
| Черт№: | | ЕКН 20 MH 5-16 2/1 H12 V8C | | | |

**Monorail trolley
standart headroom**

Кат. №:
Черт№:
ЕКН 20 MH 5-16 2/1 H12 V8C